



material: Coral®
Brush Activ, Duo

Nuway®
Tuftiguard, Tuftiguard HD, Grid

physical properties: Coral Brush Activ, Duo
roll width 78.74" (2 meters)
roll length . . . 90.22 feet (27.5 meters)
gauge 0.394" (10 mm)
pile thickness . 0.276" (7 mm)

Nuway Tuftiguard
application.. . . . internal and external
(using Plain unbuffered wiper)
wiper strips. pile - standard colors
scraper bars aluminum & PVC standard colors
height 12 mm and 17 mm
wiper strips single and double
construction open and closed

Nuway Tuftiguard HD
application internal and external
(using Plain unbuffered wiper)
wiper strips. pile - standard colors
scraper bars aluminum
height 12 mm and 17 mm
wiper strips. double only
construction closed only

Nuway Grid
application internal and external (using rubber inset)
module width . . . maximum 3000 mm
module depth . . . maximum 750 mm
height rubber: 19 mm, burford: 24 mm
classic: 23 mm, brush activ: 23 mm

recycled content: pre-consumer (post-industrial)* 6% - 9.7% Nuway Tuftiguard, Tuftiguard HD
materials & resources credit 4 15.6% Nuway Grid
1-2 points (NC, schools, CS, CI) 0% Coral
post-consumer 17.9% - 29% Nuway Tuftiguard, Tuftiguard HD
46.8% Nuway Grid
0% Coral

indoor environmental quality: adhesives meet the requirements set forth in
low emitting materials (adhesives & sealants) credit 4.1 the SCAQMD Rule #1168. Forbo FRS 920, V-885 (Coral)
1 point (NC, schools, CS, CI)

indoor environmental quality: Coral
low emitting materials
credit 4.3 (NC, schools, CS, CI)

indoor environmental quality: Coral and Nuway
indoor chemical & pollutant source control
credit 5 (NC, schools, CS, CI)

construction waste mgmt.: Coral reclamation/recycling via CARE
materials & resources credit 2, Nuway aluminum & rubber recycled locally
1-2 points (NC, schools, CS, CI)

regional material: manufacturing: Coral facility: Forbo Flooring Coral N.V., Krommenie, The Netherlands
materials & resources credit 5 Nuway facility: Forbo Flooring UK Limited, Telford, United Kingdom
1-2 points (NC, schools, CS, CI)

regional extraction/process: Coral
solution dyed PA 6Germany
aqueous dyed PA 6.6France
aqueous dyed PA 6.6The Netherlands
aqueous dyed PESThe Netherlands
backingThe Netherlands
PVC.Germany
limestone.Germany
plasticizer.The Netherlands
colorpasteFrance

Nuway Grid
aluminum carrier Spain/China
textile The Netherlands
fill in profiles United Kingdom
connecting strip. United Kingdom

Nuway Tuftiguard, Tuftiguard HD
aluminum scrapers Spain/China
galvanized steel wire. United Kingdom
tyre cord material. Luxembourg

* recycled content calculated following Federal Trade Commission (FTC) –Part 260 - GUIDES FOR THE USE OF ENVIRONMENTAL MARKETING CLAIMS

* recycled content materials shall be defined in accordance with the International Organization of Standards document, ISO 14021 - environmental labels and declarations - self-declared environmental claims (type II environmental)

note: information is based on Life Cycle Assessment (LCA) data • www.forboflooringNA.com